

## Product description

Tapel Willamette Inc. S.A.'s ready-to-use putties are an excellent alternative for repairing and recovering wood defects in boards, moldings, etc. Our Putty Face 310 Hemlock putty was designed for continuous productivity operations, compatible with DRUM FOLLOWER equipment, with great malleability, high filling capacity and fast drying, optimizing curing times before sanding, screwing and painting. Being water-based, it is environmentally and human friendly.

## Properties

Viscosity (cps, N°95 spindle at 2.5 RPM, 77°F)	150.000 – 250.000
Density (lbs/gal@ 77 °F)	15.2 – 15.6
Solids (wt.%)	80 - 84
Color (D65/10°, 1B Leneta, 50 mils)	0 – 1

## Application

This product was developed to be applied with a manual spatula. However, if you need a pneumatic application or if you have any questions, please contact Tapel Willamette Inc. S.A. Technical Service. To clean the equipment and work tools, use warm water and soap if necessary.

## Storage

The product should be stored indoors between 41 and 95°F, avoiding freezing, and at a maximum relative humidity of 85%. The product has a shelf life of 3 months from the date of manufacture. Once opened, keep the container closed to avoid superficial drying of the putty.

After a prolonged storage time, the product could present a slight syneresis or phase separation. If this occurs, just homogenize the product with a spatula before use. It is not recommended to transfer the product. If necessary consult our Technical Service.

## Health and Safety

There are no unusual health hazards associated with this product; however, the use of safety clothing, personal protective equipment and adequate ventilation are recommended. Before working with this product, we recommend reading the available information regarding hazards, uses and proper handling.

Refer to the Safety Data Sheet before using this product.