

Form Seal

Concrete Form Board Release Paint



Description

Form Seal is a waterborne paint specifically designed to meet the needs of plywood mills that manufacture plywood that will be used to make forms for concrete. The coating helps maintain the integrity of the board's edge when used under the conditions of forming concrete. Form Seal coating can be manufactured in any color and can be sprayed with many conventional paint spraying systems.

Where to Use

- Industrial manufacturer of concrete form boards
- Concrete contractors recoating form boards

Features and Benefits

- Excellent moisture protection
- Increases form board useful life
- Vibrant colors attract customers
- Available in a variety of colors
- Helps prevent checking

Typical Properties

Percent solids	45%
Viscosity, cps, ASTM D 4878	350
Wt/gal. (Kg/L)	8.77 (1.05)
Coverage, sq. ft. / U.S. gal. (sq. meters / L)	325 (8)
Color	available in many colors

Application

Apply one coat of Form Seal, as supplied, by airless spray, brush, or rolling at a wet film thickness of 4-6. For porous wood or higher performance, increased film thickness is advised. For other types of application methods, directions, and recommendations, check with your representative. Stenciling and any recoating should be done before the paint has dried completely and formed an impervious film.

Clean-Up

Clean equipment before paint dries completely. If the paint has dried, hot water, detergent, and scrubbing will be required.

Notes

This product is supplied in a ready to use form. Any addition of water to reduce viscosity may result in degradation of the product performance.

Packaging

- 5-gallon pails
- Drums
- Totes

Shelf Life

6 to 9 months when properly stored.



■ Storage

Store this product in a clean, dry and shaded or covered environment above 45°F (7.2°C). DO NOT FREEZE.

■ Health and Safety

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS please call 800-333-9826 or send an email to: sds@wilvaco.com.

■ Disclaimer of Warranty

Test results are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, no guarantee, warranty, or representation is made, intended, or implied as to the correctness or sufficiency of any information, or as to the suitability of any chemical compounds for any particular use, or that any chemical compounds or use thereof are not subject to a claim by a third party for infringement of any patent or other intellectual property right. Each user should conduct a sufficient investigation to establish the suitability of any product for its intended use. Proper application is the responsibility of the user. As with any product, the use of this product in a given application must be tested (including but not limited to field testing) in advance by the user to determine suitability. Testing is the requirement of both engineers and contractors alike. The Willamette Valley Company LLC does not warrant the application under any or all circumstances.

GWD-OTH-269 Rev 1 April 2026