

Water-based Particle Board Edge Filler



Water-based Filler for the Edges of Particle Board

Description

Our Water-based Particle Board Edge Filler is an acrylic-based wood filler used to repair defects in all types of wood. Specialized additives are incorporated to allow smooth application and the unique thixotropic characteristics enable the product to pump with ease.

Where To Use

- Edges of particle board
- industrial mill environments

Features and Benefits

- Minimal shrinkage
- Smooth application
- Easy to pump
- Paintable and stainable

Typical Properties

Percent solids by weight	68
Viscosity, cps, ASTM D 4878	300,000
Weight/gallon	15.4
Color (other colors by special order)	pine

Application

This product is formulated to be applied in industrial mill applications with an air driven Graco putty pump and automatic applicator gun or through a bullnose applicator. For other application methods or viscosity modifications, please check with your representative.

Dry Time

A think film will dry in minutes. Thicker applications may require hours to dry. Dry time depends on temperature, humidity, and thickness of film.

Clean-Up

Water-based Particle Board Edge Filler can be washed with water prior to drying. If it has dried, steam or mechanical abrasion is recommended.

Notes

This product is supplied in a ready-to-use form. Any addition of water to reduce viscosity may result in degradation of the product performance.



■ Shelf Life

6 months when properly stored.

■ Storage

Store this product in a clean, dry and shaded or covered environment.
DO NOT FREEZE.

■ Health and Safety

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS please call 800-333-9826 or send an email to: sds@wilvaco.com.

■ Disclaimer of Warranty

Test results are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, no guarantee, warranty, or representation is made, intended, or implied as to the correctness or sufficiency of any information, or as to the suitability of any chemical compounds for any particular use, or that any chemical compounds or use thereof are not subject to a claim by a third party for infringement of any patent or other intellectual property right. Each user should conduct a sufficient investigation to establish the suitability of any product for its intended use. Proper application is the responsibility of the user. As with any product, the use of this product in a given application must be tested (including but not limited to field testing) in advance by the user to determine suitability. Testing is the requirement of both engineers and contractors alike. The Willamette Valley Company LLC does not warrant the application under any or all circumstances.

GWD-DRP-205 Rev 1 April 2026

